

OUTDOOR EXTENSION CORD WITH RUGGED SAFETY SEAL LOCK

ELECTRICAL AND STRUCTURAL CHARACTERISTICS.
Cord / Cable:

 Type: SJTW 14AWG X 3C (14 AWG=2,08 mm² 3 conductors), 300 V, 105 °C
 Length: 25 ft. (7.62 m)

 Plug: *NEMA 5-15P* (2P + Ground Polarized)

 Socket: *NEMA 5-15R* (2P + Ground Polarized)

Current: 15 A

Voltage: 125 V AC

Maximum Power: 1875W

Insulated for 300V cable

MATERIALS

Base: ABS/PC

Waterproof Cover: PP

Contacts: Brass

Cord Insulation jacket: Thermoplastic

DEGREE OF PROTECTION

IP67 (IEC 60529) NEMA 4X

IMPACT RESISTANCE

IK07 (IEC 62262)

GLOW WIRE TEST

Live parts supports 750 °C

Other parts 650 °C

BALL PRESSURE TEST

Live parts supports 125 °C

APPLIED STANDARD

UL STD. 817

CSA Std. C22.2 NO.21

DIMENSIONS

Power Shell: 9.05" x 2.16" (22.99 cm x 5.49 cm)

WEIGHT

3 lb (1.36 kg)

DIELECTRIC STRENGTH

1250Vac

INSULATION RESISTANCE

>100Mohms